

BatesField GPU - Diesel Series

DC OUTPUT VOLTAGE: Standard with 28VDC outlet with 12VDC available for \$150.
Capable of **2,400~2600 Amps Peak and 800 Amps continuous** during starts.

Series	DC Output Amperage	Cost
3000	2,600 cranking amps; 300 amps for pre-start operations	<i>Call for price</i>
2000	2,500 cranking amps; 200 amps for pre-start operations	<i>Call for price</i>
1000	2,400 cranking amps; 100 amps for pre-start operations	<i>Call for price</i>

DC OUTPUT CABLE: 20' of 4/0 cable with 3 pin aircraft plug standard except for 1000 series where 15' of 2/0 cable is standard with available upgrade to 4/0 cable in lieu of 2/0 cable for \$475.

AC INPUT CABLE: 50' with customer providing plug for hangar use if hangar power is used.

PANEL METERS: AC Volt meter, Hours meter, and State of Charge meter standard on all series.
DC-Volt and DC-Amp standard on 2000 & 3000 series.
DC-Volt & DC-Amp optional on 1000 series for \$230 each.

ENGINE: Standard with world renown liquid cooled Kubota Diesel Engine.

UNDERCARRIAGE: 16" Pneumatic tires & tapered bearings. Brake available for \$549.

SHIPPING DIMENSIONS: 65"L x 49"W x 54"H; approximately 1596-1607-1615 lbs.

TERMS: Payment in full prior to shipping (deposit with order acceptable).
Freight FOB origin (Wellston, OK USA). Lead time to be agreed upon when ordering. Price does not include shipping expenses (freight) and may change without notice, so please confirm when ordering.

EQUIPPED STANDARD WITH: 120/240 VAC household type power with engine running, & ability to power aircraft from hangar power without the engine running (DUAL POWERED).



BATESFIELD GPU
930335 S. Pilot Dr.
Wellston, OK 74881

Phone: 405-258-2600
sales@gasgpu.com
Fax: 405-258-3066
www.GasGPU.com

